## ----Watchguard



## **Compact size, full performance.**

## Compact Series: NVR available in 4 channels with built-in PoE

Watchguard<sup>™</sup> Compact Series network video recorders offer Ultra HD broadcast-quality image performance, built-in PoE and rapid remote view setup via QR code, all in a compact size for home or small business applications.

- Record Ultra HD up to 8.0MP (3840 x 2160)
- Up to 80Mbps incoming bandwidth; H.265+ support
- 8TB HDD support for up to 8TB footage storage
- Remote view in seconds with setup via QR code
- Native Ultra HD live view on 4K monitors via HDMI
- Built-in PoE switches for easy install across the range
- Backup footage via network, USB or SATA devices
- Live view, playback & record via your phone/tablet





**Built-in Power over Ethernet** 



**Comprehensive Remote View** 

Model	NVR4COM3
Product Image	
<sup>9</sup> Main Processor	Industrial grade embedded processor
Operating System	Embedded Linux
Video Input	4 channels
Two-way Talk	1 channel input, 1 channel output, RCA
Interoperability	ONVIF (Profile S), CGI, SDK, RTSP
Video Output	1 x HDMI, 1 x VGA
Display Resolution Display Split	Configurable from 3840 x 2160 to 1024 x 768
	1/4
OSD	Camera title, Time, Video loss, Camera lock, Motion detection, Recording
Recording Resolution	Configurable from 8.0MP (3840 x 2160) to CIF (352 x 288)
Incoming Bandwidth	80Mbps for channels / 80Mbps for storage / 60Mbps for forwarding
Incoming Bandwidth Decoding Capability Video Compression	4 channels @ 4.0MP (25fps) H.265 + / H.265 / H.264 + / H.264
Record Modes	H.2057 / H.2057 / H.2044 / H.204 Manual / Schedule (Regular [Continuous], Motion Detection, Alarm, Timed) / Stop
Alarm Input / Output	N/A
Trigger Events	Recording, PTZ, Tour, Alarm, Video Push, Email, FTP, Snapshot, Buzzer, Screentips, Log
	General: Motion Detection, Smart Motion Detection, Video Loss, Privacy Masking, IPC Alarm
	Anomaly: Device Offline, Storage Error, Network Security Anomaly, IP/MAC Conflict
	1/4
Search Modes	Time/Date, Alarm, Motion Detection, Exact Search (to the second), Smart Search USB Device / Network
Backup Modes Ethernet	1 x RJ-45 port (10/100Mbps)
Power over Ethernet	4 ports (IEEE802.3at/af , 10/100Mbps)
¥	HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, P2P
Network Functions   Optical Interface	N/A
Max. User Access	128 users
Remote View	iOS (iPhone, iPad) / Android devices
Internal HDD	1 x SATA III port, up to 8TB
HDD Modes USB Interface	Single (no RAID compatibility)
	2 ports: Rear USB2.0 / Front USB2.0
Auxiliary Inputs	N/A
Power Supply	48VDC ~ 53VDC / 1.13A ~ 1.25A
Power Suppry Power Consumption Operating Environment Dimensions / Rack Units	< 10W (without HDD) / PoE: Max 25.5W per port, 36W total -10 ~ 55°C / 10 ~ 90%RH
Dimensions / Rack Units	260 x 225 x 48mm / 1U
Weight	0.86kg (without HDD)
Product Diagrams	

Your local Watchguard<sup>™</sup> professional: