



Superb footage over coax.

Professional Series: Motorised lens HDCVI domes available in 2.0MP

A excellent camera in all conditions with a wide range of compatible brackets, Professional Series domes from Securview offer easy adjustments via a motorised lens, all in a durable housing and low light colour footage.

- Stream up to 2.0MP (1920 × 1080) at 25fps
- 2.7~13.5mm motorised varifocal lens with fixed iris
- Smart infrared illumination, up to 60m range
- Supports audio signal via coaxial cable
- HDCVI / TVI / AHD / Analog switchable (DIP switch)
- Superb low light colour images as low as 0.001lx
- True WDR (130dB) and 3D noise reduction
- Dual voltage compatible: 12VDC and 24VAC
- IP67/IK10 for weather and vandal resistance
- 2.7 ~ 13.5mm fixed lens with 108° viewing angle



Switch Camera to Suit DVR



Superb Low Light Performance



Dual Voltage Compatible

Model		VSCVI-2DIRMD		
Camera	Image Sensor	2.0 Megapixel CMOS		
	Effective Pixels	1920 (H) × 1080 (V)		
	Signal Noise Ratio	> 65dB		
	Lens	2.7 ~ 13.5mm F1.5 Motorised Lens; Fixed Iris		
	Angle of View	108° ~ 30° (H) / 56° ~ 17° (W)		
	Focus	Auto/Manual / 0.8m Min. Focus Distance		
	Minimum Illumination	0.001Lux/F1.5, 30IRE, 0Lux IR Active		
	Electronic Shutter	1/25s ~ 1/100,000 s		
	Day/Night	Auto (ICR)		
	Infrared Range	60m		
	White Balance	Auto		
	Noise Reduction	3D NR		
	Video	Gain Control	Auto / Manual	
Lighting Compensation		BLC / HLC / WDR (130dB)		
Resolution		1080p (1920 × 1080) to 960H (960 × 576/960 × 480)		
DORI	Frame Rate	25fps (1080p and lower)		
	Transmission Distance	Audio signal transmission over coaxial cable (performed in ideal test conditions)		
	DORI Distance	Detect	44m	
		Observe	18m	
		Recognise	9m	
Identify		4m		
Interface	Audio Input	1 channel built-in microphone		
	Alarm Interface	N/A		
	Video Output	1 x CVI / TVI / AHD / CVBS by one BNC port (DIP Switch)		
	OSD Menu	N/A		
Environmental	Ingress Protection	IP67		
	Vandal Resistant	IK10		
	Housing	Metal		
	Power Input	12VDC / 24VAC		
	Power Consumption	< 9.9W		
	Dimensions	Ø126 x 100mm		
	Weight	0.65kg		
Operating Environment		-30° to 60°C / RH90% (max)		
Application	Dimensions		Junction Box	
			VSBKTA123, VSBKTA137	
			VSBKTB203W	
			Pole Mount	
		Ceiling Mount		
		VSBKTB203W + VSBKTA152E		
		VSBKTA106 + VSBKTB220C		

Your local Securview™ HDCVI solutions professional: