



180° Intruder deterrence.

Professional AI Series: 180° Fixed lens AI active deterrence bullet in 8.0MP

The Professional AI Series utilises the latest in AI machine learning technology to identify people & vehicles with superior accuracy and reliability. The active deterrence range incorporates AI detection and a variety of in-camera features to deter intruders. Upon a human or vehicle detection event, these cameras can trigger a white LED spotlight for security lighting, a flashing blue/red LED strobe and a loud siren with programmable message/tone, to deter intruders. They are ideal for active security across a variety of residential and commercial applications.

- Stream up to 8.0MP (4096 x 1860) at 20fps
- Activates spotlight, flashing light & siren, switching from IR to colour footage in response to alarm events
- 24/7 Colour low light footage as low as 0.005lx
- Up to 25m infrared, BLC/HLC & true WDR (120dB)
- Intelligent AI detection to identify people & vehicles
- Next-Gen Smart Motion Detection (SMD 4.0) & Perimeter Protection to prevent false alarms, using VIP Vision NVRs
- Dual cameras in one housing for a 180° field of view
- IP67 weather rated housing for outdoor use



180° Coverage Surveillance



Spotlight, Siren & Blue/Red Strobe



AI Human & Vehicle Detection



	Specifications		8.0MP Fixed 180° Al Deterrence Bullet	
	Ordering Information		VSIPP-8BD-ID3	
	Image Sensor		1/2.7" 8.0MP Progressive Scan CMOS	
	Effective Pixels RAM / ROM		4096 (H) x 1860 (V)	
			1GB / 128MB	
era			0.005 Lux/F1.4 (Color), 0.0005 lux/F1.4 (B/W, 30 IRE), 0 lux (IR)	
Came	Electronic Shut		1/3 ~ 1/100,000s	
	S/N Ratio		>56dB	
		~		
	Infrared System LED Illumination		1 x Infrared LED, 25m range, Auto/manual on/off control	
			1 x Spotlight (Warm White), 1 x Red & Blue Alarm Light 2.8mm F1.4 Fixed Lens	
Lens	Lens / Iris			
ت	Field of View		Horizontal: 180°, Vertical: 86°	
	Focus		Auto Focus / 0.8m Min. Focus Distance	
_	Detect (25px/m)		51m	
DOR	Observe (63px/m)		20m	
	Recognise (125px/m)		10m	
	Identify (250px/m)		5m	
	Resolution		8.0MP (4096 x 1860) to (960 x 432)	
	Frame Rate	Main		
		Sub	1200 x 530 (1 ~ 20fps)	
		Third	1920 x 860 (1 ~ 20fps)	
	Video Compression		H.265+ / H.265 / H.264+ / H.264 / H.264B / MJPEG	
o.	o Bit Rate		H.265: 6 ~ 16384Kbps / H.264: 6 ~ 16384Kbps	
ide	Bit Rate Control		Constant bit rate (CBR) / Variable bit rate (VBR)	
>	Day/Night		Auto (ICR) / Color / B&W	
	Lighting Compensation		BLC / HLC / WDR (120dB)	
	Smart Scene Adaptive		Yes	
	White Balance		Auto / Natural / Street Lamp / Outdoor / Manual	
	Gain Control		Auto	
	Noise Reduction		3D DNR	
	Video Functions		Motion Detection (4 zones), Region of Interest (4 zones), Privacy M	lasking (4 zones) Smart Illumination Defog
			Event Triggers: Motion Detection, Perimeter Protection, Video Tampering, Scene Changing, Net	
S			Perimeter Protection: People and vehicle detection u	using tripwire or intrusion rules
			Search people or vehicle detection events (Perimeter Protection)	
¥	Ethernet		RJ-45 (10/100Base-T)	
ş	Protocol		IPv4; IPv6; HTTP; TCP; UDP; ARP; RTP ; RTSP; RTCP; RTMP; SMTP; FTP; SFTP; DHCP; DNS; DDNS; QoS; UPnP; NTP; Multicast; ICMP; IGMP; NFS; SAMBA; PPPoE; SNMP; P2P	
Network	Streaming Method		Multicast	
2	Max. User Access		20 Users (Total bandwidth: 64MB)	
	Video Interface		N/A	
a)	ع Audio Interface		Built-in Mic & Built-in Speaker / Audio Compression - PCM; G.711a; G.711Mu; G.726; G.723	
Interface	Alarm Interface		1 channel in: 5mA 3-5VDC / 1 channel out: 300mA 12VDC	
ter	RS485		N/A	
=	Edge Storage		MicroSD Card (up to 256GB) / NAS / FTP / SFTP	
	Interoperability Power Supply		ONVIF (Profile S, Profile G, Profile T) / CGI	
			Deterrence: <9W (12VDC), <10.35W (PoE)	
	Power Supply Power Consumption		<pre>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>></pre>	
			<99W, <10.3W (POE) -40°C ~ +60°C / ≤95% RH	
nta				
Environmenta	Ingress Protection		IP67 N/A	
no i	Vandal Resistance			
2	Housing		Metal	
	Pan/Tilt/Rotation		Pan: 0° ~ 360°, Tilt: 0° ~ 78°, Rotation: 0° ~ 360°	
	Dimensions		Ø183mm x 99mm x 78mm	
	Net Weight		0.69kg	
Accessories		183.1 [7.21]	99.0 [3.90] 99.0 [3.90] 99.0 [3.90] 04.5 [\varnothingson 1.8] 070.1 [\varnothingson 2.76] 070.1 [\varnothingson 2.76]	Junction Box VSBKTA130E

Your local VIP Vision[™] IP solutions professional: