

## 5MP HD Intelligent LightHunter IR VF Dome Network Camera IPC3235SB-ADZK-IO



## Features

- High quality image with 5 MP, 1/2.7" CMOS sensor
- 5 MP (2880 × 1620)@30/25 fps; 4 MP (2560 × 1440)@30/25 fps; 3 MP (2304 × 1296)@30/25 fps; 1080P (1920 × 1080)@30/25 fps
- Ultra 265, H.265, H.264, MJPEG
- Intelligent perimeter protection, including cross line, intrusion, enter area, leave area detection
- Intelligent intrusion prevention system based on target classification significantly reduces false alarms caused by leaves, birds, and lights, accurately focusing on humans, vehicles, and non-motor vehicles
- Intelligent people flow counting and crowd density monitoring
- LightHunter technology ensures ultra-high image quality in low illumination environment
- 120 dB true WDR technology enables clear image in strong light scene
- Supports 9:16 corridor mode
- Built-in mic
- Alarm I/O: 1/1, audio I/O: 1/1
- Smart IR, up to 40 m (131.2 ft) IR distance
- MicroSD, up to 512 GB
- IK10 vandal resistant and IP67 protection


# Specifications

| Model                      | IPC3235SB-ADZK-10                                                                                                                                                                                                                                                                                                                                                                        |
|----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Camera                     |                                                                                                                                                                                                                                                                                                                                                                                          |
| Max Resolution             | 5 MP                                                                                                                                                                                                                                                                                                                                                                                     |
| Sensor                     | 1/2.7" CMOS                                                                                                                                                                                                                                                                                                                                                                              |
| Min. Illumination          | Color: 0.002 Lux (F1.2, AGC ON), 0 Lux with IR                                                                                                                                                                                                                                                                                                                                           |
| Day/Night                  | IR-cut filter with auto switch (ICR)                                                                                                                                                                                                                                                                                                                                                     |
| Shutter                    | Auto/Manual, 1 ~ 1/100000s                                                                                                                                                                                                                                                                                                                                                               |
| Adjustment Angle           | Pan: 0° to 355°, Tilt: 0° to 80°, Rotate: 0° to 355°                                                                                                                                                                                                                                                                                                                                     |
| S/N                        | > 56 dB                                                                                                                                                                                                                                                                                                                                                                                  |
| WDR                        | 120 dB                                                                                                                                                                                                                                                                                                                                                                                   |
| Lens                       |                                                                                                                                                                                                                                                                                                                                                                                          |
| Focal Length               | 2.7 to 13.5 mm                                                                                                                                                                                                                                                                                                                                                                           |
| Field of View (H)          | 106.3° to 32.5°                                                                                                                                                                                                                                                                                                                                                                          |
| Iris Type                  | Fixed                                                                                                                                                                                                                                                                                                                                                                                    |
| Iris                       | F1.2                                                                                                                                                                                                                                                                                                                                                                                     |
| Field of View (V)          | 53.5° to 18.0°                                                                                                                                                                                                                                                                                                                                                                           |
| Field of View (D)          | 126.0° to 38.5°                                                                                                                                                                                                                                                                                                                                                                          |
| Lens Type                  | Motorized                                                                                                                                                                                                                                                                                                                                                                                |
| DORI                       |                                                                                                                                                                                                                                                                                                                                                                                          |
| DORI Distance (Lens)       | 2.7 to 13.5 mm                                                                                                                                                                                                                                                                                                                                                                           |
| DORI Distance (Detect)     | 60.8 m to 303.8 m (199.5 ft. to 996.7 ft.)                                                                                                                                                                                                                                                                                                                                               |
| DORI Distance (Observe)    | 24.3 m to 121.5 m (79.7 ft. to 398.6 ft.)                                                                                                                                                                                                                                                                                                                                                |
| DORI Distance (Recognize)  | 12.2 m to 60.8 m (40.0 ft. to 199.5 ft.)                                                                                                                                                                                                                                                                                                                                                 |
| DORI Distance (Identify)   | 6.1 m to 30.4 m (20.0 ft. to 99.7 ft.)                                                                                                                                                                                                                                                                                                                                                   |
| Illuminator                |                                                                                                                                                                                                                                                                                                                                                                                          |
| Supplemental Light         | IR                                                                                                                                                                                                                                                                                                                                                                                       |
| Illumination Distance (IR) | 40 m (131.2 ft.)                                                                                                                                                                                                                                                                                                                                                                         |
| Light On/Off Control       | Auto/Manual                                                                                                                                                                                                                                                                                                                                                                              |
| Wavelength                 | 850 nm                                                                                                                                                                                                                                                                                                                                                                                   |
| Video                      |                                                                                                                                                                                                                                                                                                                                                                                          |
| Video Compression          | Ultra 265, H.265, H.264, MJPEG                                                                                                                                                                                                                                                                                                                                                           |
| Frame Rate                 | Main Stream: 5 MP (2880 × 1620), max. 30 fps; 4 MP (2560 × 1440), max. 30 fps; 3 MP (2304 × 1296), max. 30 fps; 1080P (1920 × 1080), max. 30 fps;<br>Sub Stream: 720P (1280 × 720), max. 30 fps; D1 (720 × 576), max. 30 fps; 640 × 360, max. 30 fps;<br>Third Stream: D1 (720 × 576), max. 30 fps; 640 × 360, max. 30 fps; 2CIF (704 × 288), max. 30 fps; CIF (352 × 288), max. 30 fps; |
| H.264 Code Profile         | Baseline profile, Main profile, High profile                                                                                                                                                                                                                                                                                                                                             |
| Video Bit Rate             | 128 Kbps to 16 Mbps                                                                                                                                                                                                                                                                                                                                                                      |
| U-code                     | Support                                                                                                                                                                                                                                                                                                                                                                                  |
| OSD                        | Up to 8 OSDs                                                                                                                                                                                                                                                                                                                                                                             |
| Privacy Mask               | Up to 4 areas                                                                                                                                                                                                                                                                                                                                                                            |

|                            |                                                                                                                                                                                                            |
|----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ROI                        | Support                                                                                                                                                                                                    |
| Video Stream               | Triple streams                                                                                                                                                                                             |
| Image                      |                                                                                                                                                                                                            |
| White Balance              | Auto, Outdoor, Fine tune, Sodium lamp, Locked, Auto2                                                                                                                                                       |
| Smart IR                   | Support                                                                                                                                                                                                    |
| Digital Noise Reduction    | 2D/3D DNR                                                                                                                                                                                                  |
| Flip                       | Normal, Flip vertical, Flip horizontal, 180°, 90° Clockwise, 90° Anti-clockwise                                                                                                                            |
| Dewarping                  | N/A                                                                                                                                                                                                        |
| HLC                        | Support                                                                                                                                                                                                    |
| BLC                        | Support                                                                                                                                                                                                    |
| Defog                      | Digital defog                                                                                                                                                                                              |
| Intelligent                |                                                                                                                                                                                                            |
| Smart Intrusion Prevention | Cross line detection, intrusion detection, enter area detection, leave area detection (support false alarm filtering and the classification of human, non-motor vehicle and vehicle)                       |
| People Counting            | Support people flow counting and crowd density detection                                                                                                                                                   |
| Statistical Analysis       | N/A                                                                                                                                                                                                        |
| Events                     |                                                                                                                                                                                                            |
| Basic Detection            | Motion detection, Ultra motion detection, Tampering alarm, Audio detection                                                                                                                                 |
| General Function           | Watermark, IP address filtering, Access policy, ARP protection, RTSP authentication, User authentication, HTTP authentication                                                                              |
| Audio                      |                                                                                                                                                                                                            |
| Audio Compression          | G.711U, G.711A, AAC-LC                                                                                                                                                                                     |
| Audio Bitrate              | G.711U/G.711A: 64 kbps, AAC-LC: 128 kbps                                                                                                                                                                   |
| Two-way Audio              | Support                                                                                                                                                                                                    |
| Suppression                | Support                                                                                                                                                                                                    |
| Sampling Rate              | G.711U/G.711A: 8 kHz, AAC-LC: 8 kHz, 16 kHz, 48 kHz                                                                                                                                                        |
| Storage                    |                                                                                                                                                                                                            |
| Edge Storage               | MicroSD, up to 512 GB                                                                                                                                                                                      |
| Network Storage            | ANR, NAS (NFS)                                                                                                                                                                                             |
| Network                    |                                                                                                                                                                                                            |
| Protocols                  | IPv4, IPv6, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL/TLS, 802.1x, SNMP, PPPoE                                                             |
| Compatible Integration     | ONVIF (Profile S, Profile G, Profile T, Profile M), API, SDK                                                                                                                                               |
| User/Host                  | Up to 32 users. 3 user levels: administrator, common user and operator                                                                                                                                     |
| Security                   | Password Protection, Strong Password, HTTPS Encryption, Export Operation Logs, Basic and Digest Authentication for RTSP, Digest Authentication for HTTP, TLS 1.2, WSSE and Digest Authentication for ONVIF |
| Client                     | EZStation, APP                                                                                                                                                                                             |
| Web Browser                | Plug-in required live view: IE 10+, Chrome 45+, Firefox 52+, Edge 79+, Plug-in free live view: Chrome 57+, Firefox 58+, Edge 16+                                                                           |
| Interface                  |                                                                                                                                                                                                            |
| Audio I/O                  | 1 Input: impedance 35 kΩ, amplitude 2 V [p-p], 1 Output: impedance 600 Ω, amplitude 2 V [p-p]                                                                                                              |
| Alarm I/O                  | 1/1                                                                                                                                                                                                        |

|                     |                                                                                                                                                                                                                                                                     |
|---------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Serial Port         | N/A                                                                                                                                                                                                                                                                 |
| Built-in Mic        | Support                                                                                                                                                                                                                                                             |
| Built-in Speaker    | N/A                                                                                                                                                                                                                                                                 |
| WIFI                | N/A                                                                                                                                                                                                                                                                 |
| Network             | 1 × RJ45 10 M/100 M Base-TX Ethernet                                                                                                                                                                                                                                |
| Video Output        | N/A                                                                                                                                                                                                                                                                 |
| Certification       |                                                                                                                                                                                                                                                                     |
| EMC                 | CE-EMC (EN 55032, EN 61000-3-3, EN IEC 61000-3-2, EN 55035)<br>FCC (FCC 47 CFR part15 B)                                                                                                                                                                            |
| Safety              | CE LVD (EN 62368-1)<br>CB (IEC 62368-1)<br>UL/CUL (UL 62368-1, CAN/CSA C22.2 No. 62368-1)                                                                                                                                                                           |
| Environment         | CE-RoHS (2011/65/EU;(EU)2015/863); WEEE (2012/19/EU);                                                                                                                                                                                                               |
| Protection          | IP67 (IEC 60529)<br>IK10 (IEC 62262)                                                                                                                                                                                                                                |
| General             |                                                                                                                                                                                                                                                                     |
| Power               | DC 12 V±25%, PoE (IEEE 802.3af)                                                                                                                                                                                                                                     |
| Power Consumption   | Max. 7.0 W                                                                                                                                                                                                                                                          |
| Power Interface     | Ø5.5 mm coaxial power plug                                                                                                                                                                                                                                          |
| Dimensions          | Ø148.0 mm × 111.4 mm (Ø5.8" × 4.4") (Ø × H)                                                                                                                                                                                                                         |
| Weight              | 0.97 kg (2.12 lb.)                                                                                                                                                                                                                                                  |
| Material            | Metal                                                                                                                                                                                                                                                               |
| Working Environment | -30 °C to 60 °C (-22 °F to 140 °F), Humidity: ≤ 95% RH (non-condensing)                                                                                                                                                                                             |
| Storage Environment | -30 °C to 60 °C (-22 °F to 140 °F), Humidity: ≤ 95% RH (non-condensing)                                                                                                                                                                                             |
| Surge Protection    | 6 KV                                                                                                                                                                                                                                                                |
| Reset Button        | Support                                                                                                                                                                                                                                                             |
| Web Client Language | 20 Languages: Traditional Chinese, English, Simplified Chinese, Polish, German, Russian, French, Korean, Dutch, Czech, Portuguese (Europe), Portuguese (Brazil), Japanese, Thai, Turkish, Spanish (Latin America), Spanish (Europe), Hungarian, Italian, Vietnamese |

Dimensions



Accessories

|                                                                                            |                                                                       |                                                                                             |
|--------------------------------------------------------------------------------------------|-----------------------------------------------------------------------|---------------------------------------------------------------------------------------------|
| <b>TR-JB04-C-IN</b><br>Junction Box for 323 Series<br>Fix-dome(Support wiring from behind) | <b>TR-FM152-A-IN</b><br>In-ceiling Bracket for 323 Series<br>Fix-dome | <b>TR-SM04-IN</b><br>Switch Box Adapter for 323 Series<br>Fix-dome                          |
|                                                                                            |                                                                       |                                                                                             |
| <b>TR-A01-IN</b><br>NPT 3/4" Waterproof Cable Gland                                        | <b>TR-UC08-C-V2</b><br>Bullet&Dome Corner Mounting Bracket            | <b>TR-JB07/WM04-B-IN-V2</b><br>4 Inch Back Hole Hemisphere Wall Mounting Assembling Bracket |
|                                                                                            |                                                                       |                                                                                             |

|                                                                                   |                                                                                   |                                                                                     |
|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| <b>TR-WM04-IN-V2</b><br>4 Inch Hemisphere Wall Mounting Bracket                   | <b>TR-CM24-IN</b><br>Dome Pendent Mounting Bracket(Indoor)                        | <b>TR-SE24-A-IN</b><br>Dome Pendent Mounting Pole 500mm                             |
|  |  |  |
| <b>TR-SE24-IN</b><br>Dome Pendent Mounting Pole 200mm                             | <b>TR-UP06-C-IN-V2</b><br>Pole Mounting Bracket for Bullet Junction<br>Box Only   |                                                                                     |
|  |  |                                                                                     |

# Unlimited New View

**Zhejiang Uniview Technologies Co., Ltd.**



<http://www.uniview.com>



[overseasbusiness@uniview.com](mailto:overseasbusiness@uniview.com); [globalsupport@uniview.com](mailto:globalsupport@uniview.com)



No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China



©2023-2025 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

\*Product specifications and availability are subject to change without notice.

Despite our best efforts, technical or typographical errors may exist in this document. Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.