Camera & security light in one.

Professional AI Series: Motorised AI bullet cameras in 4.0MP, 6.0MP & 8.0MP

The Professional AI CCTV camera I3 range combines the latest in AI surveillance and a security light into one housing. During AI people and vehicle detection events, the camera will trigger a warm LED light to deter intruders and capture footage in full colour. Quickly search and track people & vehicles throughout entire sites across all Acupick CCTV cameras in your security system.

- Stream up to 8.0MP (3840 x 2160) at 25fps
- Up to 60m infrared range; true day/night (auto ICR)
- Intelligent search across all Acupick cameras
- Warm LED light triggers on person/vehicle detection
- H.265 encoding for efficient storage & streaming
- Back/highlight compensation & true WDR (120dB)
- MicroSD slot for recording at the edge up to 256GB
- AI weather and anti-flicker scene self-adaption
- Next-Gen Smart Motion Detection (SMD 4.0) & Perimeter Protection to prevent false alarms, using VIP Vision NVRs

Record up to 4K in Real Time



AI Human & Vehicle Detection



Intelligent people & vehicle search

Achieve more than security.™

Visit www.vipvision.au for the latest in IP surveillance.

INFRONT TECHNOLOGIES

Supplied by INFRONT TECHNOLOGIES

Phone 1300 736 970

sales@infronttech.com.au · infronttech.com.au

For more information call or email — Australia-wide sales, technical support and warranty service.

	Specifications		4.0MP Motorised AI Bullet	6.0MP Motorised AI Bullet	8.0MP Motorised AI Bullet
	Ordering Information		**VSIPP-4BIRMG-I3**	**VSIPP-6BIRMG-I3**	**VSIPP-8BIRMG-I3**
Camera	Image Sensor		1/2.9" 4.0MP Progressive Scan CMOS	1/2.7" 6 .0MP Progressive Scan CMOS	1/2.7" 8.0MP Progressive Scan CMOS
	Effective Pixels		2688 (H) x 1520 (V)	3288 (H) × 1850 (V)	3840 (H) x 2160 (V)
	RAM / ROM		1GB / 256MB		
	Min Illumination		0.005 Lux/F1.4 (Color), 0.0005 Lux/F1.4 (B/W), 0 lux (illuminator on)	0.007 Lux/F1.4 (Color), 0.0007 Lux/F1.4 (B/W), 0 lux (illuminator on)	0.007 Lux/F1.4 (Color), 0.0007 Lux/F1.4 (B/W), 0 lux (illuminator on)
	Illuminator		4x warm LED light, 4x Infrared LED, 60m range, Auto/manual on/off control		
	S/N Ratio		> 56dB		
Lens	Lens / Iris		2.7 ~ 13.5mm F1.4 Motorised Varifocal Lens with Fixed Iris		
	Field of View		Horizontal: 104°~29°, Vertical: 54°~16°	Horizontal: 114°~32°, Vertical: 58°~17°	Horizontal: 114°~32°, Vertical: 58°~17°
	Focus		Auto Focus / 0.1m Min. Focus Distance		
DORI	Detect (25px/m)		64m (wide) / 210m (tele)	85m (wide) / 280m (tele)	85m (wide) / 280m (tele)
	Observe (63px/m)		26m (wide) / 84m (tele)	34m (wide) / 112m (tele)	34m (wide) / 112m (tele)
	Recognise (125px/m)		13m (wide) / 42m (tele)	17m (wide) / 56m (tele)	17m (wide) / 56m (tele)
	Identify (250px/m)		6m (wide) / 21m (tele)	8m (wide) / 28m (tele)	8m (wide) / 29m (tele)
Video	Resolution		4.0MP (2688 x 1520) to CIF (352 x 288)	6.0MP (3288 × 1850) to CIF (352 x 288)	8.0MP (3840 x 2160) to CIF (352 x 288)
	Frame Rate	Main	4.0MP (1 ~ 25fps)	6.0MP (1 ~ 25fps)	8.0MP (1 ~ 25fps)
		Sub	1080p (1 ~ 25fps)		
		Third	1080p (1 ~ 25fps)		
	Video Compression		H.265; H.264; H.264H; H.264B; MJPEG; Smart H.265+; Smart H.264+; AI H.265; AI H.264		
	Bit Rate		H.265: 3 ~ 16384Kbps / H.264: 3 ~ 16384Kbps		
	Bit Rate Control		Constant bit rate (CBR) / Variable bit rate (VBR)		
	Day/Night		Auto (ICR) / Color / B&W		
	Lighting Compensation		BLC / HLC / WDR (120dB) / AI SSA		
	White Balance		Auto / Natural / Street Lamp / Outdoor / Manual / Regional Custom		
	Gain Control		Auto		
	Noise Reduction		3D DNR		
	Picture Control		Mirror / Flip (0°, 90°, 180°, 270°) (support 90°/270° with 4.0MP and lower)		
IVS	Video Functions		Motion Detection (4 zones), Region of Interest (4 zones), Privacy Masking (8 zones), Smart Infrared		
	AI Functions		**Smart Motion Detection (SMD 4.0):** People and vehicle detection using motion detection **Perimeter Protection:** People and vehicle detection using tripwire or intrusion rules **Acupick:** Search by people/vehicle attribute (e.g colour) and track their movements		
	Intelligent Search		Search people or vehicle detection events (SMD 4.0, Perimeter Protection)		
Network	Ethernet		RJ-45 (10/100Base-T)		
	Protocol		IPv4; IPv6; HTTP;TCP; UDP; ARP; RTP; RTSP; RTCP; RTMP; SMTP; FTP; SFTP; DHCP; DNS; DDNS; QoS; UPnP; NTP; Multicast; ICMP; IGMP; NFS; SAMBA; PPPoE; SNMP; P2P		
	Streaming Method		Multicast		
	Max. User Access		20 Users (Total bandwidth: 64MB)		
Interface	Video Interface		N/A		
	Audio Interface		1 input (RCA Port) / 1 output (RCA Port) / Built-in MIC / Audio Compression - G.711a; G.711Mu; PCM; G.726; G.723		
	Alarm Interface		1 channel in: 5mA 3-5VDC / 1 channel out: 300mA 12VDC		
	Edge Storage		FTP / SFTP / NAS / MicroSD Card (up to 512GB)		
	Interoperability		ONVIF / P2P / CGI		
Environmental	Power Supply		12VDC / PoE (802.3af)		
	Power Consumption		Max: <9.3W (12VDC), 11.9W (PoE)	Max: <9.9W (12VDC), 12.5W (PoE)	Max: <9.9W (12VDC), 12.5W (PoE)
	Operating Conditions		-40°C ~ +60°C / ≤95% RH		
	Ingress Protection		IP67		
	Housing		Metal		
	Pan/Tilt/Rotation		Pan: 0° ~ 360°, Tilt: 0° ~ 90°, Rotation: 0° ~ 360°		
	Dimensions		239mm x 79mm x 75mm		
	Net Weight		0.84kg		

Application



Junction Box	
VSBKTA130E	VSBKTA135
Pole Mount	Corner Mount
VSBKTA135 or VSBKTA130E + VSBKTA152E	VSBKTA130E + VSBKTA151

Your local VIP Vision™ IP solutions professional:

INFRONT TECHNOLOGIES

Supplied by INFRONT TECHNOLOGIES

Phone 1300 736 970

sales@infronttech.com.au · infronttech.com.au

For more information call or email — Australia-wide sales, technical support and warranty service.