


# NC119XA Security Camera

Tons of features packed into one well priced camera. Excellent proactive deterrent using Red and Blue light to strobe. Speak to talk through the mobile app or set off the siren. This camera has Smart Motion Detection that will pick up humans and vehicles to reduce false alarms.

4 MEGA PIXELS

2.8mm LENS

## Specifications

| | |
|---|---|
| **Camera Type** | Turret |
| **Image Sensor** | 1/3" Progressive CMOS |
| **Maximum Video Resolution (Megapixels)** | 4 |
| **Maximum Video Resolution** | 2560 x 1440 |
| **Frames Per Second (FPS)** | 25 |
| **Lens** | 2.8 mm (H.FOV: 95°) |
| **Lens Type** | Fixed |
| **Maximum Night IR Distance (M)** | 25 |
| **LED** | IR, Red & Blue, White |
| **Video Compression** | H.265+, H.265, H.264+, H.264, MJPEG |
| **ONVIF depends on firmware version** | ONVIF (Profile S/G/T) 21.12 or greater, HTTP API |
| **Accessories** | IV2422X, IV2433X, IV2444X, IV2455X, IV2457X, IV2477X, IV2480X |
| **Outdoor Use** | Yes |
| **IP Rating** | IP67 |
| **IK Rating** | IK08 |
| **Day/Night Mode** | Full color (Auto) |
| **Image Enhancement** | Flip mode, Brightness, Contrast, Saturation, Sharpness, Hue, Mirror, Angle Flip, Back Light, White Balance, Shutter, Time Exposure, Defog, 3D Noise Reduction |
| **Intelligent Video (IVS)** | Smart Motion Detection, Perimeter Intrusion Detection, Line Crossing Detection |
| **Edge Recording microSD/SDHC Card** | Micro SD/SDHC Card |
| **Multiple Streams (encode format)** | 2 Streams |
| **Software** | Device Search/Config Tool, Surveillance Client (CMS/VMS), Mobile app (QR code) |
| **Protocols** | TCP/IP, UDP, HTTP, HTTPS, DHCP, FTP, RTP/RTSP, DNS, DDNS, NTP, PPPOE, UPNP, SMTP, SNMP, P2P (QR code) |
| **Language** | English, French, Spanish, Portuguese, German, Italian, Greek, Danish, Finnish, Russia, Hebrew, Turkish, Bulgarian, Arabic, Korean, Japanese, Thai, Hindi, Romanian, Dutch, Polish |
| **Cloud option (camera only)** | Dropbox |
| **Audio Streaming** | Yes (microphone and speaker included) |
| **Ethernet** | Ethernet (10/100 Base-T) |
| **Power Over Ethernet** | Yes |
| **Power Supply** | Power over Ethernet IEEE 802.3af, DC12V |
| **Power Consumption** | < 5W |
| **Connectors** | RJ-45, DC Power Input, Reset Button |
| **Operating Environment** | -30~+55°C/less than ≤ 95% RH |
| **In The Box** | Printed quick user guide, installation template, mounting screws and plugs |
| **Product Dimensions (H x W x L) mm** | 90 x 100 x 100 |
| **Packaging Dimensions (H x W x L) mm** | 120 x 135 x 135 |
| **Weight (Net) kg** | 0.22 |
| **Weight (Gross) kg** | 0.55 |
| **Warranty** | 3 Year Warranty |

https://www.ivsecurity.com.au/product/nc119xa/

Updated 20/10/2026

INFRONT TECHNOLOGIES

**Supplied by INFRONT TECHNOLOGIES**

**Phone 1300 736 970**

sales@infronttech.com.au · infronttech.com.au

*For more information call or email — Australia-wide sales, technical support and warranty service.*