

NC323XD-BLK Security Camera

SONY Starvis sensor, Human and vehicle tracking, Extra photos/ frames per second (FPS), Improvements to Wide Dynamic Range (WDR) to handle difficult lighting. Locking mechanism on housing. Supports SD card. New tech Infra-red LEDs.

8 MEGA PIXELS | IVS | PVR | SONY STARVIS SENSOR

Specifications

Camera Type	Turret
Image Sensor	1/2.8" 8MP Progressive CMOS
Maximum Video Resolution (Megapixels)	8
Maximum Video Resolution	3840 x 2160
Frames Per Second (FPS)	20
Lens	3.6 mm (H.FOV: 88°)
Lens Type	Fixed
Maximum Night IR Distance (M)	30
LED	IR
Video Compression	H.265+, H.265, H.264+, H.264, MJPEG
ONVIF depends on firmware version	ONVIF (Profile S/G/T) 21.12 or greater, HTTP API
Accessories	IV2422X, IV2433X, IV2444X, IV2455X, IV2457X, IV2477X, IV2480X
Outdoor Use	Yes
IP Rating	IP67
IK Rating	IK10
Day/Night Mode	Auto
Image Enhancement	Flip mode, Brightness, Contrast, Saturation, Sharpness, Hue, Corridor Mode, Mirror, Angle Flip, Back Light, White Balance, Shutter, Time Exposure, Defog, 3D Noise Reduction
Intelligent Video (IVS)	Perimeter Intrusion Detection, Face Recognition, Human & Vehicle Detection, Line Crossing Detection, Stationary Object Detection, Crossing Counting, Heat Map, Crowd Density Detection, Queue Length Detection, License Plate Detection, Rare sound detection
Edge Recording microSD/SDHC Card	Micro SD/SDHC Card
Multiple Streams (encode format)	3 Streams
Software	Device Search/Config Tool, Surveillance Client (CMS/VMS), Mobile app (QR code)
Protocols	TCP/IP, UDP, HTTP, HTTPS, DHCP, FTP, RTP/RTSP, DNS, DDNS, NTP, PPPOE, UPNP, SMTP, SNMP, P2P (QR code)
Language	English, French, Spanish, Portuguese, German, Italian, Greek, Danish, Finnish, Russia, Hebrew, Turkish, Bulgarian, Arabic, Korean, Japanese, Thai, Hindi, Romanian, Dutch, Polish
Cloud option (camera only)	Dropbox
Audio Streaming	Yes (microphone included)
Ethernet	Ethernet (10/100 Base-T)
Power Over Ethernet	Yes
Power Supply	Power over Ethernet IEEE 802.3af, DC12V
Power Consumption	< 7W
Connectors	RJ-45, DC Power Input, Reset Button
Operating Environment	-30~+55°C/less than ≤ 95% RH
In The Box	Free Software available from FTP, Printed quick user guide, installation template, mounting screws and plugs
Product Dimensions (H x W x L) mm	100 x 100 x 100
Packaging Dimensions (H x W x L) mm	120 x 140 x 140
Weight (Net) kg	0.44
Weight (Gross) kg	0.53
Warranty	3 Year Warranty

https://www.ivsecurity.com.au/product/nc323xd/

Updated 20/10/2026

INFRONT TECHNOLOGIES

Supplied by INFRONT TECHNOLOGIES

Phone 1300 736 970

sales@infronttech.com.au · infronttech.com.au

For more information call or email — Australia-wide sales, technical support and warranty service.