SR-PSU-12v2A

12V 2A plug-pack, centre positive 2.1 mm plug, suits Swann DVRs and 12V cameras



Output	12V DC, 2A (24W)
Input	100-240V AC, 50/60Hz, 0.5A max (label of the unit pictured)
DC plug	Barrel plug, 2.1 mm inside, 5.5 mm outside; centre +12V, outer sleeve GND (centre positive)
Type	Switch mode plug-pack, efficiency level IV
Mains	Australian pins: plugs straight into a power point. Australian approved; C-Tick mark on the unit pictured
DC lead	About 1.8 m
Use	Indoor use, I.T.E. equipment
Suits	Swann 4 and 8-channel DVRs (SWDVK-4, SWDVR-4, SWDVK-8, SWDVR-8 families) whose adaptor reads 12V 2A, centre positive, 2.1 mm
Also runs	12V DC CCTV cameras drawing 2A or less in total (through a splitter for several)
Not for	DVRs needing 3A or more, 48V Swann NVRs, 2.5 mm DC sockets
Unit pictured	Model NLD200120W1S. Model number and case shape may differ between batches; the 12V 2A centre positive rating is the same
Meter check	DC volts, red probe inside the plug, black probe on the outer sleeve: about +12V

Generic supply that suits Swann systems; not made by Swann.

Only connect this supply to equipment that takes 12V DC, 2A or less, centre positive, on a 2.1 mm plug.

Indoor use. Do not open the case. Cutting or rewiring the DC lead voids the warranty.

Figures from the rating label of the unit pictured and our product details. No manufacturer datasheet is published for this supply. Questions: 1300 736 970, sales@infronttech.com.au.

INFRONT TECHNOLOGIES

Supplied by INFRONT TECHNOLOGIES

Phone 1300 736 970

sales@infronttech.com.au · infronttech.com.au

For more information call or email — Australia-wide sales, technical support and warranty service.