SR-PSU-12V1A

12V 1A camera power supply, centre positive 2.1 mm plug, suits Swann SWPRO cameras



Output	12V DC, 1A (12W)
Input	100-240V AC, 50/60Hz, 0.35A max
DC plug	Barrel plug, 2.1 mm inside, 5.5 mm outside; centre +12V, outer sleeve GND (centre positive)
Type	Switch mode plug-pack, efficiency level IV
Mains	Australian pins: plugs straight into a power point. Approved for the Australian market
DC lead	At least 1 m (confirm with us if you need an exact length)
Camera budget	All cameras on the supply together 1A or less, e.g. 2 cameras at 500 mA or 3 at 300 mA (splitter sold separately)
Suits	12V DC CCTV cameras with a centre positive 2.1 mm plug, including Swann SWPRO analogue cameras
Not for	DVRs needing 2A or more, PoE network cameras, 24V AC cameras, 48V NVRs, 2.5 mm DC sockets
Model number	Varies between batches (earlier stock CS-1201000); the 12V 1A centre positive rating is the same
Meter check	DC volts, red probe inside the plug, black probe on the outer sleeve: about +12V

Generic supply that suits Swann systems; not made by Swann.

Only connect this supply to equipment that takes 12V DC, 1A or less in total, centre positive, on a 2.1 mm plug.

Indoor use. Do not open the case. Cutting or rewiring the DC lead voids the warranty.

Figures from our product details. No manufacturer datasheet is published for this supply. Questions: 1300 736 970, sales@infronttech.com.au.