



# Peak quality & versatility.

## Professional Series: Motorised lens HDCVI bullet available in 8.0MP

With superior 80m infrared illumination, 4K resolution and ultra low light colour, the G-Body series from Securview captures clear footage at all hours, featuring a motorised varifocal lens for easy remote image adjustment.

- Stream up to UHD/4K/8.0MP (3840 x 2160) at 15fps
- Motorised varifocal 3.7~11mm lens with fixed iris
- Large 1/2" sensor for excellent low light performance
- Smart infrared illumination, up to 80m range
- HDCVI / AHD / TVI / CVBS switchable via DIP switch
- Up to 700m video transmission over coaxial cable
- True WDR (120dB) and 2D/3D noise reduction
- IP67 rated weather resistant metal housing



**Ultra HD Recording Over Coax**



**Compatible With Any Coax DVR**



**Superb Low Light Performance**

Model		VSCVI-8BIRMG	
Camera	Camera Style	G Body	
	Image Sensor	1/2" 8.0 Megapixel CMOS	
	Effective Pixels	3840 (H) x 2160 (V)	
	Signal Noise Ratio	> 65dB	
	Lens	3.7mm ~ 11mm F1.5 Motorised Lens, fixed iris	
	Angle of View	112° (wide) ~ 46° (tele)	
	Focus	Fixed / 1.8m Min. Focus Distance	
	Minimum Illumination	0.005 Lux at F1.5 (Colour) / 0 Lux IR Active	
	Electronic Shutter	1/4 ~ 1/100,000s	
	Day/Night	Auto (ICR) / Colour / B&W	
	Infrared Range	80m	
	White Balance	Auto / Manual	
	Noise Reduction	2D / 3D	
	Gain Control	Auto	
Lighting Compensation	BLC / HLC / WDR (120dB)		
Video	Resolution	8.0MP (3840 x 2160) to CIF (352 x 288)	
	Frame Rate	15fps (8.0MP) / 20fps (6.0MP) / 25fps (4.0MP and lower)	
	Transmission Distance	Rated for up to 700m via 75-3 coaxial cable (performed in ideal test conditions)	
DORI	DORI Distance	Detect	83m (wide) / 190m (tele)
		Observe	33m (wide) / 76m (tele)
		Recognise	17m (wide) / 38m (tele)
		Identify	8m (wide) / 19m (tele)
		Audio Input	Built-in Microphone / 1 Input
Interface	Alarm Interface	N/A	
	Video Output	1 x HDCVI / AHD / TVI / Composite video output (switchable via DIP switch)	
	Synchronisation	Internal	
	OSD Menu	Support	
	Ingress Protection	IP67	
Environmental	Vandal Resistant	N/A	
	Housing	Aluminium	
	Power Input	12VDC	
	Power Consumption	< 12.5W	
	Dimensions	244 x 90 x 90mm	
	Weight	0.76kg	
	Operating Environment	-30° to 60°C / RH90% (max)	
Accessories	Diagram		
	Accessories	<p>Refer to bracket compatibility guide for complete list</p>	
	Models	Junction Box (VSBKTA130E)	Pole Mount (VSBKTA130E + VSBKTA152E)